



Engine U9

Overview

Chip

NXP Ucode 9 (U9)

EPC

96bits

USER

Null

Antenna Dimensions

44*28mm

Frequency Band

860MHz-960MHz

International Standard


EPCglobal C1 Gen2 and ISO18000-6C

Industry Segments


Apparel

Applications

Anti-Counterfeiting Traceability



Xindeco IOT Engine U9 inlay uses NXP U9 series chips, which are functional and flexible in a 44*28mm size, making them one of the top choices for RFID marking applications. The inlay is ideal for retail items such as apparel and daily necessities, and can be quickly integrated with inventory and logistics applications. The excellent performance of the Engine series in the paper antenna version is still stable.



Address

Building No. 6, Xindeco Industrial Park, No. 2-16 Hongxi South Road,Xiangan District, Xiamen, 361101, China

Lot 28, Jalan Permata 1/1, Arab Malaysia Industrial Park, 71800 Nilai, Negeri Sembilan

Contact

Email sales@xindecoiot.com Web www.xindecoiot.com











Technical features

| | Dry | Wet | Paper-face |
|------------------------|---------------------------|---------------------------|-----------------------|
| Product Code | CTU45001-485D | CTU45001-485W | CTU45001-485L |
| Antenna Size | 44*28mm | 44*28mm | 44*28mm |
| | 1.73*1.10in | 1.73*1.10in | 1.73*1.10in |
| Finish Size | - | 47*31mm | 47*31mm |
| | - | 1.85*1.22in | 1.85*1.22in |
| Web Width | 56mm | 53mm | 53mm |
| | 2.20in | 2.09in | 2.09in |
| Pitch | 34.925mm | 34.925mm | 34.925mm |
| | 1.38in | 1.38in | 1.38in |
| Antenna Material | Aluminium | Aluminium | Aluminium |
| Front Face | - | PET Clear/PET White/Paper | Paper |
| Inlay Substrate | PET Clear/PET White/Paper | PET Clear/PET White/Paper | PET Clear/Paper |
| Inlay Adhesive | - | Permanent | Permanent |
| Liner | - | Paper | Paper |
| Operating Temperrature | -20℃/50℃ -4°F/+122°F | -20℃/50℃ -4°F/+122°F | -20℃/50℃ -4°F/+122°F |
| Shelf Life Time | @20% to 80% RH | @20% to 80% RH | @20% to 80% RH |
| | 2/2/1 years @+25°C/40%RH | 1 years @+25°C/40%RH | 1 years @+25°C/40%RH |
| Inlays/Roll | 12000pcs | 3000pcs | 3000pcs |
| Final Insperction | 100% tested | 100% tested | 100% tested |
| | | | |







